

# Wessels company

# SUBMITTAL NVA-SERIES

**Models:** NVA-1000 to NVA-15000

**Submittal Sheet No.** A-1013B **Rev.** 1 4/26/2019

Job Name Location	Submitted By Approved By Order No.	Date Date Date
Engineer Contractor Sales Rep.	Notes	

## **Description:**

Wessels NVA Tanks are ASME removable bladder type pre-charged expansion tanks. They are designed to absorb the expansion forces and control the pressure in heating/cooling systems. The system's expanded water (fully compatible with water/glycol mixtures) is contained in a full acceptance heavy-duty butyl bladder that prevents tank corrosion and waterlogging problems. All NVA expansion tanks can be installed vertically or horizontally.

#### Construction:

Shell: Carbon Steel

Bladder: Heavy Duty Butyl

System Connection: Carbon Steel

### **Design Parameters:**

Maximum Design Temperature: 240°F Maximum Design Pressure: 125 PSIG\*

\*200 & 250 PSIG available

MODEL NUMBER	PART NUMBER	TANK VOLUME (GAL)	TAGGING INFORMATION	QUANTITY
NVA-1000	22001000	264		
NVA-1200	22001200	317		
NVA-1400	22001400	370		
NVA-1600	22001600	422		
NVA-2000	22002000	528		
NVA-2500	22002500	660		
NVA-3000L	22003000	792		
NVA-3000S	22003001	792		
NVA-4000	22004000	1056		
NVA-5000	22005000	1320		
NVA-7500	22007500	1980		
NVA-10000	22009999	2640		
NVA-15000	22000000	3963		

Typi	ical	Spe	ecific	cati	ion:

Furnish and install, as shown on plans, a \_\_\_\_\_\_\_\_gallon \_\_\_\_\_\_" diameter X \_\_\_\_\_" (high) pre-charged steel expansion tank with heavy-duty butyl bladder. The tank shall have NPT system connections and a 0.302"-32 charging valve connection (standard tire valve) to facilitate the on-site charging of the tank to meet system requirements. The tank shall be fitted with lifting rings and a floor mounting skirt for vertical installation. The tank must be constructed in accordance with most recent addendum of Section VIII Division 1 of the ASME Boiler and Pressure Vessel Code.

Each tank shall be Wessels model number NVA-\_\_\_\_\_ or approved equal









**Models:** NVA-1000 to NVA-15000

**Submittal Sheet No.** A-1013B **Rev.** 1 4/26/2019





NVA-1000 thru NVA-15000

# **Dimensions & Weights:**

	DIMENSIONS IN INCHES							
Model Number	Α	В	SYSTEM CONNECTION	CHARGING VALVE	Е	F	G	Approx. Shipping Weight (lbs)
			С	D				
NVA-1000	36	87			30	8	8 1/2	735
NVA-1200		98 1/2	]					745
NVA-1400		112	3					900
NVA-1600	48	84	]		42	9	8 3/4	1210
NVA-2000		96	]					1305
NVA-2500		114					8 1/4	1430
NVA-3000L		134	]	0.302-32NC				1671
NVA-3000S	72	93	]		54	10		2169
NVA-4000		115						2638
NVA-5000		138	4					3246
NVA-7500		140			60	11		4080
NVA-10000		172						4920
NVA-15000		243						6000

# Notes:

- Tanks are factory pre-charged at 12 psi and field adjustable.
- California code-sight glass is available upon request.
- Available with mounting clips.
- Tanks installed horizontally must have the sustem connection below the horizontal centerline of the tank.

