

SUBMITTAL

WVN NON-REMOVABLE-SERIES

AIR & DIRT SEPARATOR

Models: WVN-2N thru WVN-12N Submittal Sheet No. D-1110B

/16

Job Name	 Submitted By	 Date
Location	 Approved By	 Date
	 Order No.	 Date
Engineer	 Notes	
Contractor	 	
Sales Rep.	 	

Description

Wessels WVN-N (Non-Removable) series Air & Dirt Separators are designed to eliminate entrained air and separate debris associated with start-up and maintenance of any hydronic systems. The design incorporates a skim valve, used to eliminate floating debris, and an air vent to automatically release air from the separator.

Construction

Shell: Carbon Steel

Coalescing Medium: Stainless Steel Blow Down Valve (optional): Bronze Skim Valve (optional): Bronze Vent (optional): Cast Iron

Performance Limitations

Maximum Design Temperature: 250°F Maximum Design Pressure: 150 PSIG*


*125, 200 & 250 PSIG available

Model Number	Part Number	Max Flow (GPM)	Tagging Information	Quantity
WVN-2N	74080020	69		
WVN-2N-NPT	74080021	69		
WVN-2.5N	74080025	108		
WVN-2.5N-NPT	74080026	108		
WVN-3N	74080030	144		
WVN-3N-NPT	74080031	144		
WVN-4N	74080040	255		
WVN-5N	74080050	398		
WVN-6N	74080060	570		
WVN-8N	74080080	945		
WVN-10N	74080100	1440		
WVN-12N	74080120	2100		

Typical Specification

Furnish and install, as shown on plans, a WVN	N Air & Dirt Separator as manufactured by Wessels
Company. Each separator must be designed with a blow	down valve, skim valve, and automatic air vent. The
separator must also utilize in its design a stainless steel o	coalescing medium to aid in the separation of air and
dirt in the systems entrained water. The separator mus	st be constructed and stamped for 150 PSI working
pressure @ 250°F.	

Each air separator shall be Wessels model number WVN-_____-N or approved equal.



WVN-2N thru WVN-12N

Dimensions & Weights

	Dimensions in Inches					Approx		
Model Number	Connection Size	Α	В	С	D	Е	Shipping Wt (lbs)	
WVN-2N	- 2	4.4/0		15 1/4			76	
WVN-2N-NPT] 2	4 1/2	23	9	11 1/0		70
WVN-2.5N	2.5	E 1/0	23	15 3/4	11 1/2		99	
WVN-2.5N-NPT	2.5	2.5 5 1/2	10 1/2			90		
WVN-3N	- 3		6 1/2	20 1/4			114	
WVN-3N-NPT			0 1/2	29	12 3/4	14 1/2	0 5/0	100
WVN-4N	4	8 1/2		20 5/8		8 5/8	194	
WVN-5N	5	10	39	27 3/4	40.4/0	10.1/2		230
WVN-6N	6	12		21 3/4	19 1/2		255	
WVN-8N	8	16	49	33 5/8	24 1/2		514	
WVN-10N	10	20	65 37 1/2 32 1/2	32 1/2		770		
WVN-12N	12	24	76	42 1/2	38		1080	

Notes

• Trim package is optional.